# Control plate for TEMPOMATIC 4 for urinals

Ref. 430036

Recessed electronic battery-operated valve - For urinals

## DESCRIPTION

**Control plate for TEMPOMATIC 4 for urinals** - Ref. 430036

TEMPOMATIC 4 electronic valve F½", kit 2/2.
Battery-operated with CR 123 Lithium 6V batteries.
Solenoid valve enables opening and closing of water.
Black control plate 145 x 145mm in shock-resistant vitro-ceramic glass with integrated electronics.
Shock-resistant infrared presence detection sensor.
Detection delay is 10 seconds.
3 programmes (rinsing volume can be adjusted according to urinal type).
High frequency mode (exclusive to DELABIE):
- Short rinse after each user.
- Additional rinse after the period of increased frequency of use.
Hygienic duty flush every 24 hours (can be adjusted to 12 hours or OFF) after last use: prevents vacuums.
Flow rate pre-set at 0.15 L/sec at 3 bar, can be adjusted.
TEMPOMATIC 4 F½" valve compatible with sea water, rain water and grey water.
Installation in waterproof housing with waterproof collar, transformer, filter and stopcock.
Suitable for people with reduced mobility.
30-year warranty.
Order with frame system references 543006 for urinals Ø 35mm, 543006D for urinals with flexible ½" or with recessed housing 430PBOX.

## ADVANTAGES

- Total hygiene: no manual contact
- 3 rinsing programmes and high-frequency mode
- Hygienic duty flush
- 123 Lithium 6V batteries

## TECHNICAL CHARACTERISTICS

**Control plate for TEMPOMATIC 4 for urinals** - Ref. 430036

| | |
|---|---|
| Supply | 6V batteries |
| Technology | Electronic |
| Length | 145mm |
| Width | 145mm |
| Finish | Black wall plate in shock-resistant vitro-ceramic glass |
| Norms | |
| Warranty | |