TEMPOFLUX 2 control plate for WCs

Ref. 578212

Soft-touch operation time flow valve



DESCRIPTION

TEMPOFLUX 2 control plate for WCs - Ref. 578212

Control plate for TEMPOFLUX 2 time flow direct flush, kit 2/2: Flush system without cistern, directly connected to pipework. Ø 195mm chrome-plated metal wall plate. Concealed mechanical fixing of the wall-plate.

6L single flush.

Soft-touch operation.

For walls 10 to 35mm or 30 to 60mm.

Upstream supply pipes: minimum \emptyset 20mm required at all points (including connectors).

Base flow rate: 1L/sec at 1 bar dynamic pressure. Complies with European standard EN 12541 class II.

30-year warranty.

Order with frame system references 578305DE or 578405DE.

ADVANTAGES



Soft-touch operation



Direct flush: no water stagnation




Flush is instantly available

TECHNICAL CHARACTERISTICS

TEMPOFLUX 2 control plate for WCs - Ref. 578212

Connector	3/4"
Technology	Time flow
Depth	Walls from 10 to 35mm
Flow rate	6L
Diameter	Ø 195mm
Finish	Chrome-plated metal
Norms	B
Warranty	30 E WARRANTY



© DELABIE https://www.delabie.co.uk