## **TEMPOMATIC 5 electronic** basin tap

Ref. 44900015

Mains supply



## **DESCRIPTION**

TEMPOMATIC 5 electronic basin tap - Ref. 44900015

Basin-mounted electronic tap:

230/6V recessed mains supply.

Reduced-stagnation solenoid valve and electronic unit integrated into the body of the tap.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm. Scale-resistant flow straightener.

Duty flush (~60 seconds every 24 hours after last use).

Active, infrared presence detection, sensor at the end of the spout optimises detection.

Chrome-plated metal body.

PEX flexibles M½" with stopcocks, filters, non-return valves and conical inlets Ø 15mm.

Fixing reinforced by two stainless steel rods.

Anti-blocking security.

Suitable for people with reduced mobility.

30-year warranty.

## **ADVANTAGES**



Total hygiene: no manual contact



90% water savings



Anti-bacterial proliferation duty flush



Recessed mains supply

## TECHNICAL CHARACTERISTICS

TEMPOMATIC 5 electronic basin tap - Ref. 44900015

Supply	230/6V mains supply
Connector	M½" Ø 15mm
Technology	Electronic
Drop height	74mm
Spout length	105mm
Flow rate	3 lpm
Finish	Chrome-plated metal
Norms	ACS (JWRAS)
Warranty	30 WARRANTY

