

TEMPOFLUX 3 AB flush system

Ref. 763256

Anti-blocking direct flush WC valve



DESCRIPTION

TEMPOFLUX 3 AB flush system - Ref. 763256

Flush system without cistern: directly connected to pipework.

For walls $\leq 200\text{mm}$.

Soft-touch operation.

AB anti-blocking system: flush only takes place once the push-button is released.

Time flow ~ 7 seconds.

Vacuum breaker.

Stopcock and volume/flow rate adjustment, activation unit and cartridge are all integrated and accessible via the service duct.

Chrome-plated metal push-button.

Shock-resistant mechanism.

In-line inlet $M\frac{3}{4}"$.

Complies with European standard EN 12541 (class II acoustic level).

Cut-to-size threaded rod.

Upstream supply pipes: minimum $\varnothing 20\text{mm}$ required at all points (including connectors).

Base flow rate: 1L/sec at 1 bar dynamic pressure.

Compatible with rain water.

Suitable for rimless WC pans without flow rate regulation and suitable for people with reduced mobility.

30-year warranty.

ADVANTAGES



Anti-blocking system



Cross wall installation



Direct flush: limits the risk of leaks



Flush is powerful and instantly available

TECHNICAL CHARACTERISTICS

TEMPOFLUX 3 AB flush system - Ref. 763256

Connector	$\frac{3}{4}"$
Technology	Time flow
Norms	 
Warranty	

