

Recessed sequential thermostatic shower mixer with angled outlet

Ref. H9633

SECURITHERM mixer with no non-return valves, kit 2/2






DESCRIPTION

Recessed sequential thermostatic shower mixer with angled outlet - Ref. H9633

Recessed thermostatic shower mixer with angled outlet, kit 2/2 : Sequential thermostatic mixer: opens and closes with cold water. Mixer with no non-return valves on the inlets (reduces bacterial development). No risk of cross flow between the hot and cold water. Sequential mixer with anti-scalding failsafe: shuts off automatically if cold water supply fails. Avoids cold showers: shuts off automatically if hot water supply fails. Securitouch thermal insulation prevents burns. Scale-resistant sequential thermostatic cartridge adjusts the flow rate and temperature. Temperature control from cold water up to 39°C with pre-set maximum temperature limiter set at 39°C. Thermal shocks are possible. Flow rate regulated at 9 lpm (mixer only), 6 lpm at 3 bar with a shower head. ERGO control knob. Filters integrated in the M3/4" inlets. Bright polished stainless steel cover plate 166 x 166mm. Mixer ideal for use in healthcare facilities, retirement and care homes, hospitals and clinics. Sequential mixer suitable for people with reduced mobility. Shower mixer with 30-year warranty. Order with the waterproof recessing housing ref. H96CBOX.

TECHNICAL CHARACTERISTICS

Recessed sequential thermostatic shower mixer with angled outlet - Ref. H9633

Technology	SECURITHERM Securitouch sequential thermostatic mixer
Flow rate	Flow rate regulated at 9 lpm (mixer only), 6 lpm at 3 bar with shower head
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	ACS 
Warranty	
Repairability	

ADVANTAGES



Sequential: opens/closes with cold water



Maximum hygiene: no non-return valves



SECURITHERM: optimal anti-scalding safety



Thermostatic: total temperature stability

