

# TEMPOMIX 3 AB time flow mixer

Ref. 794000AB

Soft-touch operation, stopcocks, AB system





## DESCRIPTION

TEMPOMIX 3 AB time flow mixer - Ref. 794000AB

Deck-mounted single control time flow basin mixer:  
Soft-touch operation.  
Temperature control and operation on the push-button.  
Time flow ~7 seconds.  
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.  
Tamperproof scale-resistant flow straightener.  
Chrome-plated metal body.  
PEX flexibles F3/8" with stopcocks, filters and non-return valves.  
Fixing reinforced by 2 stainless steel rods.  
Adjustable maximum temperature limiter.  
AB anti-blocking system: water will flow only when the push-button is released.  
Suitable for people with reduced mobility.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

TEMPOMIX 3 AB time flow mixer - Ref. 794000AB

Connector	F3/8"
Technology	Time flow
Drop height	70mm
Spout length	105mm
Flow rate	3 lpm
Norms	 <b>ACS</b>
Warranty	

## ADVANTAGES



Exceptional water savings: 85%



Anti-blocking system



Soft-touch operation



Sleek design

