

# BINOPTIC 2 electronic tap

Ref. 383000

Mains, for slim panels, stopcock, L. 140mm



## DESCRIPTION

**BINOPTIC 2 electronic tap - Ref. 383000**

Satin finish electronic basin tap for slim panels:  
230/6V mains supply.  
Reduced-stagnation solenoid valve and electronic unit are integrated into the body of the tap.  
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.  
Scale-resistant aerator.  
Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).  
Wall-mounted stainless steel tap.  
Presence detection sensor at the end of the spout optimises detection.  
Anti-blocking security.  
Spout with smooth interior and low water volume (reduces bacterial development).  
Set detection distance, duty flush and launch thermal shocks manually.  
Suitable for people with reduced mobility.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

**BINOPTIC 2 electronic tap - Ref. 383000**

Supply	230/6V mains supply
Connector	M½"
Technology	Electronic
Spout length	140mm
Flow rate	3 lpm
Finish	Satin
Warranty	

## ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Anti-bacterial proliferation duty flush



LED diagnostic aids

