

# BINOPTIC 2 electronic tap

Ref. 384110

Mains, recessed, L. 220mm



## DESCRIPTION

**BINOPTIC 2 electronic tap - Ref. 384110**

Recessed chrome-plated electronic basin tap:  
230/6V mains supply.  
Reduced-stagnation solenoid valve and electronic unit are integrated into the body of the tap.  
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 - 6 lpm.  
Scale-resistant aerator.  
Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).  
Wall-mounted stainless steel tap.  
Active, infrared presence detection, sensor at the end of the spout optimises detection.  
Anti-blocking security.  
Spout with smooth interior and low water volume (reduces bacterial development).  
Set duty flush and launch thermal shocks manually.  
Suitable for people with reduced mobility.  
30-year warranty.

## ADVANTAGES



Total hygiene: no manual contact



90% water savings



Anti-bacterial proliferation duty flush



Sleek design

## TECHNICAL CHARACTERISTICS

**BINOPTIC 2 electronic tap - Ref. 384110**

Supply	230/6V mains supply
Connector	M $\frac{1}{2}$ "
Technology	Electronic
Spout length	220mm
Flow rate	3 lpm
Finish	Chrome-plated
Warranty	

