

BIOFIL 2 month spout filter

Ref. 20040

Sterile



DESCRIPTION

BIOFIL 2 month spout filter - Ref. 20040

Single use removable BIOFIL anti-Legionella and all-germ spout.
Can be installed instead of removable BIOCLIP spouts (no need for any tools or to shut off the water supply).

Membrane type: tubular microfiltration.

Membrane material: Polyethylene.

Pore cut-off threshold: 0.1µm nominal-rated, sterilising grade.

Qualified water volume per duration of use: 6,000L.

Filtration flow rate: 6 lpm at 3 bar (filter only, excludes any flow rate restriction in the mixer/tap).

Maximum upstream pressure at the point-of-use: 5 bar.

Maximum lifespan: 2 months after installation.

Compatible with and resistant to thermal and chemical shocks.

Sterile filter.

Weight: 40g.

Reference for a single unit. Must be ordered in multiples of 10.

Packaged in boxes of 10 units.

ADVANTAGES



Anti-Legionella and all-germ



Easy to install without tools



Lifespan: 2 months after installation



Maintains drop height

TECHNICAL CHARACTERISTICS

BIOFIL 2 month spout filter - Ref. 20040

Technology	Point-of-use filtration
Length	138mm
Flow rate	6 lpm at 3 bar
Norms	ACS WRAS KTW BWGL

