

## BIOFIL 4-month tap head filter

Ref. 20451

Sterile



### DESCRIPTION

#### BIOFIL 4-month tap head filter - Ref. 20451

DELABIE anti-Legionella and all-germ tap filter, laminar flow.  
 Device made from ABS.  
 Membrane type: tubular microfiltration.  
 Membrane made from polyethylene.  
 Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade.  
 Qualified water volume per duration of use: 12,000 litres.  
 Filtration flow rate: 4.6 lpm at 1 bar, 7.6 lpm at 3 bar and 9.4 lpm at 5 bar (filter only, excludes any flow rate restriction in the tap).  
 Space saving, suitable for taps with a low spout height: H. 63mm - Ø. 56mm  
 Controlled management of retro-contamination: protective skirt and angled connector for optimal positioning (filter position can be adjusted so the water does not flow directly on to the waste).  
 Maximum upstream pressure at the point-of-use: 5 bar.  
 Maximum lifespan: 4 months after installation.  
 Resistance to thermal shocks: 70°C for 30 minutes.  
 Resistance to chemical shocks: active chlorine levels up to 100 ppm for 4 hours cumulative.  
 Sterile filter.  
 CE Class Is medical device.  
 Reference for a single unit. Must be ordered in multiples of 10.  
 Packaged in boxes of 10 units.

### TECHNICAL CHARACTERISTICS

#### BIOFIL 4-month tap head filter - Ref. 20451

Technology	Point-of-use filtration
Height	63mm
Flow rate	4.6 lpm at 1 bar, 7.6 lpm at 3 bar and 9.4 lpm at 5 bar
Diameter	56 mm
Lifespan	4 months

Norms



### ADVANTAGES

-  Anti-Legionella and all-germ
-  Space saving
-  Optimised position: angled connection
-  Lifespan: 4 months after installation

