

BIOFIL 2 month spout filter

Ref. 30040

Non-sterile



DESCRIPTION

BIOFIL 2 month spout filter - Ref. 30040

Single use removable BIOFIL anti-Legionella and all-germ spout.
Can be installed instead of removable BIOCLIP spouts (no need for any tools or to shut off the water supply).
Membrane type: tubular microfiltration.
Membrane material: Polyethylene.
pore cut-off threshold: 0.1µm nominal-rated, sterilising grade.
Filtration surface area 1,200cm².
Filtration flow rate: 6 lpm at 3 bar (filter only, excludes any flow rate restriction in the mixer/tap).
Maximum upstream pressure at the point-of-use: 5 bar.
Maximum lifespan: 2 months after installation.
Compatible with and resistant to thermal and chemical shocks.
Non-sterile filter.
Weight: 40g.
Reference for a single unit. Must be ordered in multiples of 10.
Packaged in boxes of 10 units.

TECHNICAL CHARACTERISTICS

BIOFIL 2 month spout filter - Ref. 30040

Technology	Point-of-use filtration
Length	138mm
Flow rate	6 lpm at 3 bar
Norms	ACS   

ADVANTAGES



Anti-Legionella and all-germ



Easy to install without tools



Lifespan: 2 months after installation



Maintains drop height

