

# BINOPTIC 2 electronic tap

Ref. 37300015

Mains, deck-mounted, stopcock, H. 100mm



## DESCRIPTION

**BINOPTIC 2 electronic tap - Ref. 37300015**

Deck-mounted satin finish electronic basin tap:  
230/6V mains supply.  
Reduced stagnation solenoid valve and electronic unit integrated into the body of the tap.  
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.  
Scale-resistant aerator.  
Adjustable duty flush (~60 seconds every 24 hours after the last use).  
Stainless steel tap, 100mm high for inset basins.  
Sensor at the end of the spout optimises presence detection.  
PEX flexible with stopcock, filter and conical inlet Ø 15mm.  
Fixing reinforced by 2 stainless steel rods.  
Anti-blocking security.  
Smooth interior spout with low water volume (limits bacterial niches).  
Set presence detection range, duty flush and launch thermal shocks manually.  
Suitable for people with reduced mobility.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

**BINOPTIC 2 electronic tap - Ref. 37300015**

Supply	230/6V mains supply
Connector	M $\frac{1}{2}$ " Ø 15mm
Technology	Electronic
Drop height	100mm
Flow rate	3 lpm
Finish	Satin
Warranty	

## ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Anti-bacterial proliferation duty flush



Sleek design

