

# BINOPTIC 2 electronic tap

Ref. 37400015

Mains, deck-mounted, stopcock, H. 170mm



## DESCRIPTION

**BINOPTIC 2 electronic tap - Ref. 37400015**

Deck-mounted satin electronic basin tap:  
230/6V mains supply.  
Reduced stagnation solenoid valve and electronic unit integrated into the body of the tap.  
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.  
Scale-resistant aerator.  
Adjustable duty flush (~60 seconds every 24 hours after the last use).  
Stainless steel tap, 170mm high for semi-recessed basins.  
Presence detection sensor at the end of the spout optimises detection.  
PEX flexible with stopcock, filter and conical inlet Ø 15mm.  
Fixing reinforced by 2 stainless steel rods.  
Anti-blocking security.  
Smooth spout interior with low water volume (reduces bacterial development).  
Set detection distance, duty flush and launch thermal shocks manually.  
Suitable for people with reduced mobility.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

**BINOPTIC 2 electronic tap - Ref. 37400015**

|             |   |
|-------------|---|
| Supply      | 230/6V mains supply   |
| Connector   | M½" Ø 15mm  |
| Technology  | Electronic  |
| Drop height | 170mm   |
| Flow rate   | 3 lpm   |
| Finish      | Satin   |
| Warranty    |  |

## ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Anti-bacterial proliferation duty flush



LED diagnostic aids

