

BINOPTIC 2 electronic tap

Ref. 37401015

Mains, deck-mounted, stopcock, H. 170mm



DESCRIPTION

BINOPTIC 2 electronic tap - Ref. 37401015

Deck-mounted satin electronic basin tap:
230/6V mains supply.
Reduced stagnation solenoid valve and electronic unit integrated into the body of the tap.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.
Scale-resistant aerator.
Adjustable duty flush (~60 seconds every 24 hours after the last use).
Stainless steel tap, 170mm high for semi-recessed basins.
Presence detection sensor at the end of the spout optimises detection.
PEX flexibles Ø 15mm for compression fittings with filters and stopcock.
Fixing reinforced by 2 stainless steel rods.
Anti-blocking security.
Smooth spout interior with low water volume (reduces bacterial development).
Set detection distance, duty flush and launch thermal shocks manually.
Suitable for people with reduced mobility.
30-year warranty.

TECHNICAL CHARACTERISTICS

BINOPTIC 2 electronic tap - Ref. 37401015

Supply	230/6V mains supply
Connector	M½" Ø 15mm
Technology	Electronic
Drop height	170mm
Flow rate	3 lpm
Finish	Chrome-plated
Warranty	

ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Anti-bacterial proliferation duty flush



LED diagnostic aids

