

# BINOPTIC MIX 2 electronic basin mixer

Ref. 47300015

Mains supply, deck-mounted, stopcocks, H. 100mm

## DESCRIPTION

**BINOPTIC MIX 2 electronic basin mixer - Ref. 47300015**

Deck-mounted satin finish electronic basin mixer:  
230/6V mains supply.  
Reduced stagnation solenoid valve and electronic unit integrated into the body of the mixer.  
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.  
Scale-resistant aerator.  
Adjustable duty flush (~60 seconds every 24 hours after the last use).  
Stainless steel mixer, 100mm high for inset basins.  
Sensor at the end of the spout optimises presence detection.  
PEX flexibles Ø 15mm for compression fittings with stopcocks, filters and non-return valves.  
Fixing reinforced by 2 stainless steel rods.  
Anti-blocking security.  
Smooth spout interior with low water volume (reduces bacterial development).  
Side temperature control with adjustable maximum temperature limiter.  
Set presence detection range, duty flush and launch thermal shocks manually.  
Suitable for people with reduced mobility.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

**BINOPTIC MIX 2 electronic basin mixer - Ref. 47300015**

Supply	230/6V mains supply
Connector	M $\frac{1}{2}$ " Ø 15mm
Technology	Electronic
Drop height	100mm
Flow rate	3 lpm
Finish	Satin
Warranty	



## ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Anti-bacterial proliferation duty flush



LED diagnostic aid

