TEMPOMIX 3 time flow basin mixer

Ref. 794120

Soft-touch operation, deck-mounted, H.255




DESCRIPTION

TEMPOMIX 3 time flow basin mixer - Ref. 794120

Deck-mounted single control time flow basin mixer:
Soft-touch operation.
Temperature control and operation on the push-button.
Time flow pre-set at ~7 seconds.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 3 to 6 lpm.
Tamperproof scale-resistant flow straightener.
Chrome-plated stainless steel body, 255mm height for deck-mounting.
F3/8" PEX flexibles with filters and non-return valves.
Fixing reinforced by back-nut.
Adjustable maximum temperature limiter.
Suitable for people with reduced mobility.
30-year warranty.

ADVANTAGES

- Exceptional water savings: 85%
- Soft-touch operation
- Reinforced fixings with back-nut
- Sleek design



TECHNICAL CHARACTERISTICS

TEMPOMIX 3 time flow basin mixer - Ref. 794120

Connector	F3/8"
Technology	Time flow
Drop height	250mm
Flow rate	3 lpm
Finish	Chrome
Norms	BELGAQUA, WRAS, ACS, DVGW
Warranty	30 YEAR WARRANTY