## TEMPOMATIC 4 waterproof housing for showers

Ref. 443SBOX

Mains supply, kit 1/2



## **DESCRIPTION**

TEMPOMATIC 4 waterproof housing for showers - Ref. 443SBOX

TEMPOMATIC 4 waterproof housing for showers kit 1/2: Collar with waterproof seal.

Hydraulic connection to the outside and maintenance from the front. Adjusts to all types of installation (rails, solid walls, panels).

Compatible with wall finishes 10 - 120mm (while maintaining the minimum recessing depth of 93mm).

Integrated stopcocks, flow regulator, filter, non-return valve and cartridge, accessible from the front.

Supplied in 2 kits: to allow secure system flush without sensitive elements. 30-year warranty.

Order with control plate only, reference 443228 or complete shower kit, reference 443229.

## **ADVANTAGES**



For recessed installation



Adjustable and modular waterproof housing



System tested to over 500,000 operations




100% waterproof housing

## TECHNICAL CHARACTERISTICS

TEMPOMATIC 4 waterproof housing for showers - Ref. 443SBOX

Connector	1/2"
Technology	Electronic
Depth	10 - 120mm
Width	170mm
Norms	ACS
Warranty	30 g



© DELABIE https://www.delabie.co.uk