

## Be-Line® exposed shower pack

Ref. 511MEXP2

DOC M pack

### DESCRIPTION

**Be-Line® exposed shower pack - Ref. 511MEXP2**

Matte white powder-coated aluminium DOC M exposed shower pack. 19 items:

- 2 Drop-down support rails, length 850mm.
  - 3 Grab bars, with ergonomic flat front face, length 600mm.
  - 2 Grab bars, with ergonomic flat front face, length 450mm.
  - 1 Lift-up shower seat.
  - 1 Backrest, depth 150mm.
  - 1 aluminium finish coat hook.
  - 1 SECURITHERM single lever sequential thermostatic exposed shower mixer with top outlet and Ø 16mm exposed shower column with reinforced collar.
  - 1 Chrome-plated TONIC JET shower head, tamperproof and scale-resistant, with automatic flow rate regulator set at 6 lpm.
  - 1 Exposed diverter valve.
  - 1 Multi-mode shower kit with 1 single jet shower head, 1 sliding soap dish for riser rails, 1 sliding shower head holder and 1 flexible shower hose.
  - 1 Grab bar for use as shower riser rail, length 600mm.
  - 1 Shower hose retaining collar: retains shower hose correctly.
- 30-year warranty.  
CE marked.

### TECHNICAL CHARACTERISTICS

**Be-Line® exposed shower pack - Ref. 511MEXP2**

|          |                                                                                                                                                                         |
|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Length   | Grab bars: 450 and 600mm; Drop-down support rails: 850mm                                                                                                                |
| Finish   | Matte white powder-coated aluminium                                                                                                                                     |
| Norms    |   |
| Warranty |                                                                                      |



### ADVANTAGES



Innovative design suitable for all users



Maximum safety: tested to over 200kg