SECURITHERM sequential thermostatic shower mixer

Ref. 9630

Thermostatique mixer with no non-return valves, bottom outlet

DESCRIPTION

SECURITHERM sequential thermostatic shower mixer - Ref. 9630

SECURITHERM sequential thermostatic shower mixer.
Sequential thermostatic mixer: opens and closes with cold water.
Mixer with no non-return valves on the inlets (reduces bacterial proliferation).
No risk of cross flow between the hot and cold water.
Sequential mixer with anti-scalding failsafe: shuts off automatically if cold water supply fails.
Prevents cold showers: shuts off automatically if hot water supply fails.
Securitouch thermal insulation prevents burns.
Scale-resistant sequential thermostatic cartridge adjusts the flow rate and the temperature.
Temperature adjusts from cold water up to 39°C with temperature limiter set at 39°C.
Thermal shocks are possible.
Body with smooth interior and low water volume (reduces bacterial proliferation).
Flow rate regulated at 9 l/min.
Chrome-plated brass body and Hygiene lever L. 100mm.
M1/2" bottom outlet.
Mixer with no wall connectors with filters integrated in the inlets, F3/4".
Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
Sequential mixer suitable for people with reduced mobility.
Shower mixer with 30-year warranty.

ADVANTAGES

- Sequential: opens/closes with cold water
- Maximum hygiene: no non-return valves
- SECURITHERM: optimum anti-scalding safety
- Thermostatic: temperature stability

TECHNICAL CHARACTERISTICS

SECURITHERM sequential thermostatic shower mixer - Ref. 9630

Technology	SECURITHERM Securitouch sequential thermostatic shower mixer
Length	184mm
Flow rate	9 lpm at 3 bar
Temperature limiter	YES
Finish	Chrome-plated brass
Norms	ACS WRAS
Warranty	30 YEAR WARRANTY
Repairability	50 YEARS REPAIRABILITY