

# Wall-mounted sequential mechanical basin mixer

Ref. 2437S

Sequential mechanical mixer with fixed spout



## DESCRIPTION

Wall-mounted sequential mechanical basin mixer - Ref. 2437S

Wall-mounted sequential mechanical basin mixer.  
Sequential over a 90° range: opens and closes with cold water.  
Fixed flat under-spout, L. 200mm with hygienic flow straightener suitable for fitting a BIOFIL point-of-use filter.  
Securitouch thermal insulation prevents burns.  
Ø 35mm ceramic cartridge.  
Pre-set maximum temperature limiter.  
Body and spout with smooth interiors and low water volume (reduces bacterial development).  
Flow rate regulated at 5 lpm.  
Hygiene lever L. 150mm.  
Supplied with 2 wall-mounted standard connectors, M1/2" M3/4".  
Suitable for people with reduced mobility.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

Wall-mounted sequential mechanical basin mixer - Ref. 2437S

|                     |                                                                                     |
|---------------------|-------------------------------------------------------------------------------------|
| Connector           | M1/2"                                                                               |
| Technology          | Sequential mechanical mixer                                                         |
| Spout length        | 200mm                                                                               |
| Flow rate           | 5 lpm                                                                               |
| Temperature limiter | YES                                                                                 |
| Finish              | Chrome-plated brass                                                                 |
| Warranty            |  |
| Repairability       |  |

## ADVANTAGES



Sequential: opens and closes with cold water



Maximum hygiene: manages biofilm



No non-return valves



No manual contact: Hygiene lever

