

# TEMPOMIX 3 time flow washbasin mixer

Ref. 794110S

Soft-touch, deck-mounted, satin finish stainless steel, H.175

## DESCRIPTION

TEMPOMIX 3 time flow washbasin mixer - Ref. 794110S

Single control time flow deck-mounted washbasin mixer:  
Soft touch.  
Temperature adjustment and activation with the button.  
Time flow pre-set to ~7 seconds, adjustable from 6 to 9 seconds.  
Pre-set flow rate at 3l/min at 3 bar, adjustable from 3 to 6l/min.  
Vandal-resistant, scale-resistant aerator.  
Satin finish stainless steel body.  
175mm height for semi-recessed basin.  
F3/8" PEX flexibles with filters and non-return valves.  
Reinforced fixing with locking nut.  
Pre-set temperature limiter.  
Adapted for accessibility.  
30 year warranty.

## TECHNICAL CHARACTERISTICS

TEMPOMIX 3 time flow washbasin mixer - Ref. 794110S

|             |                                                                                                                                                                                                                                                                                                                                                 |
|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connector   | F3/8"                                                                                                                                                                                                                                                                                                                                           |
| Technology  | Time flow                                                                                                                                                                                                                                                                                                                                       |
| Drop height | 175mm                                                                                                                                                                                                                                                                                                                                           |
| Flow rate   | 3 l/min                                                                                                                                                                                                                                                                                                                                         |
| Finish      | Satin finish                                                                                                                                                                                                                                                                                                                                    |
| Norms       |     |
| Warranty    |                                                                                                                                                                                                                                                              |



## ADVANTAGES



Design



Soft-touch



Reinforced fixings with locking nut



Exceptional water savings of 85%

