

TEMPOMATIC MIX electronic mixer

Ref. 20464T1

Swivelling spout H. 165mm L. 160mm

2025 UK public price excluding VAT: £681.66

DESCRIPTION

TEMPOMATIC MIX electronic mixer - Ref. 20464T1

Electronic basin mixer with high, swivelling spout L. 160mm H. 165mm. Independent IP65 electronic control unit.

123 6V Lithium battery-operated.

Flow rate pre-set at 4 lpm at 3 bar, can be adjusted from 1.5 to 6 lpm, with scale-resistant flow straightener suitable for BIOFIL point-of-use filters.

Body and spout with smooth interiors (reduces niches where bacteria can develop).

Adjustable duty flush (pre-set flush for approximately 60 seconds every 24 hours after the last use, to prevent stagnation in the water supply if the system is not used for prolonged periods).

Thermal shocks are possible.

Shock-resistant infrared presence detection sensor.

Chrome-plated solid brass body and spout; fixing reinforced via 2 stainless steel rods.

Hygiene lever L. 100mm controls temperature.

PEX flexibles with and M3/8" solenoid valves.

Anti-blocking security.

The solenoid valves are upstream of the mixing chamber.

30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC MIX electronic mixer - Ref. 20464T1

Supply	6V Lithium batteries
Connector	M3/8"
Technology	Electronic
Height	280mm
Drop height	165mm
Spout length	160mm
Flow rate	4 lpm
Finish	Chrome-plated brass

Norms



ADVANTAGES



Automatic anti-bacterial duty flush




Smooth body/spout interior, reduces bacteria



Split delivery, flow rate pre-set at 4 lpm



Infrared detection with no manual contact



Warranty	
Repairability	