## SECURITHERM EP pressurebalancing basin mixer

Ref. 2521LEP

Single hole mechanical mixer H. 85mm, L. 135mm

2025 UK public price excluding VAT: £232.41



SECURITHERM EP pressure-balancing basin mixer - Ref. 2521LEP

Deck-mounted mechanical basin mixer with pressure-balancing basin mixer. Single hole mixer with spout H. 85mm L. 135mm fitted with BIOSAFE hygienic spout outlet.

 $\ensuremath{\text{\emptyset}}$  40mm ceramic cartridge with pressure-balancing with pre-set maximum temperature limiter.

Anti-scalding safety: HW flow rate is reduced if cold water supply fails (and vice versa).

Flow rate limited to 5 lpm at 3 bar.

Hygiene control lever L. 150mm.

Without pop-up waste.

F3/8" PEX flexibles with filters and non-return valves.

Fixing reinforced by 2 stainless steel rods.

Mechanical mixer with SECURITHERM pressure-balancing ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Single hole mixer suitable for people with reduced mobility.

Mixer with 30-year warranty.

## TECHNICAL CHARACTERISTICS

SECURITHERM EP pressure-balancing basin mixer - Ref. 2521LEP

| Connector           | F3/8"                           |
|---------------------|---------------------------------|
| Technology          | SECURITHERM EP mechanical mixer |
| Height              | 185mm                           |
| Drop height         | 85mm                            |
| Spout length        | 135mm                           |
| Flow rate           | 5 lpm at 3 bar                  |
| Temperature limiter | Yes                             |
| Finish              | Chrome-plated brass             |
| Norms               | ACS BELGAGUA                    |
|                     |                                 |
| Warranty            | 30 St                           |



## **ADVANTAGES**



HW flow rate reduced if CW fails



EP: reduces temperature variations



Hygiene: BIOSAFE hygienic outlet with no grid



Hygiene control lever requires no manual contact

