

Mechanical mixer for sinks or troughs

Ref. 2564T3

Single control single hole tall mixer with ceramic cartridge

2026 UK public price excluding VAT: £280.39

DESCRIPTION

Mechanical mixer for sinks or troughs - Ref. 2564T3

Deck-mounted mechanical mixer.
Single control single hole mixer with swivelling spout H. 305mm L. 140mm.
Tall mixer with hygienic flow straightener suitable for fitting a BIOFIL point-of-use filter.

Ø 35mm classic ceramic cartridge with pre-set maximum temperature limiter.
Body and spout with smooth interiors (reduces bacterial development).

No risk of cross flow between the hot and cold water.

No non-return valves on the inlets.

Thermal shocks are easy to undertake without removing the control lever or shutting off the cold water.

Flow rate limited to 9 lpm at 3 bar.

Chrome-plated brass body and base.

Hygiene control lever L. 185mm requires no manual contact.

PEX flexibles F3/8".

Fixings reinforced by 2 stainless steel rods and back-nuts.

Mechanical mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.

Single hole mixer suitable for people with reduced mobility.

Mixer with 30-year warranty.

TECHNICAL CHARACTERISTICS

Mechanical mixer for sinks or troughs - Ref. 2564T3

Connector	F3/8"
Height	462mm
Drop height	305mm
Spout length	140mm
Flow rate	9 lpm at 3 bar
Temperature limiter	Yes
Finish	Chrome-plated brass
Norms	  
Warranty	
Repairability	



ADVANTAGES



Hygiene: smooth interior reduces bacteria



Thermal shock without removing the control lever



Optimised drop height and spout length



Optimised drop height and spout projection

