

SECURITHERM EP pressure-balancing shower mixer

Ref. 2739EPS

Wall-mounted single control mixer, sculptured lever

2024 UK public price excluding VAT: £291.07








DESCRIPTION

SECURITHERM EP pressure-balancing shower mixer - Ref. 2739EPS

Wall-mounted single control mechanical shower mixer.
Wall-mounted single control mixer with Securitouch thermal insulation to prevent burns.
Ø 40mm pressure-balancing ceramic cartridge with pre-set maximum temperature limiter.
Anti-scalding safety: HW flow is reduced if CW supply fails (and vice versa). Constant temperature regardless of variations in pressure and flow rate in the system.
Body with smooth interior and low water volume.
Flow rate regulated at 9 lpm.
Chrome-plated brass body and sculptured control lever.
M1/2" shower outlet with integrated non-return valve.
Mixer with offset standard wall connectors, M1/2" M3/4".
Filters and non-return valves.
Mechanical mixer with SECURITHERM pressure-balancing ideal for healthcare facilities, nursing homes, hospitals and clinics.
Shower mixer suitable for people with reduced mobility.
Mixer with 30-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM EP pressure-balancing shower mixer - Ref. 2739EPS

| | |
|---------------------|---|
| Connector | M1/2" |
| Technology | SECURITHERM EP mechanical mixer |
| Width | 182mm |
| Flow rate | 9 lpm |
| Temperature limiter | Yes |
| Finish | Chrome-plated brass |
| Norms | ACS     |
| Warranty |  |

ADVANTAGES



HW flow rate reduced if CW fails



Pressure-balancing: reduces temperature variations



Hygiene: smooth interior reduces bacteria



Maximum hygiene: low water volume

