Shower kit with thermostatic mixer

Ref. H9630KIT

Riser kit with thermostatic mixer with no non-return valves

2025 UK public price excluding VAT: £501.39



Shower kit with thermostatic mixer - Ref. H9630KIT

Shower riser kit with thermostatic sequential mixer.

Shower riser rail with SECURITHERM thermostatic shower mixer.

Thermostatic sequential mixer: opens and closes with cold water.

Mixer with no non-return valves on the inlets (reduces bacterial proliferation). No risk of cross flow between hot and cold water.

Sequential mixer with anti-scalding failsafe: shuts off automatically if cold or

Sequential mixer with anti-scalding failsare: snuts off automatically if cold o hot water supply fails.

Securitouch thermal insulation prevents burns.

Scale-resistant, thermostatic sequential cartridge:

Temperature control from cold water up to 39°C with maximum temperature limiter set at 39°C.

Thermal shocks are possible.

Body with smooth interior and low water volume.

Flow rate regulated at 9 lpm.

Chrome plated brass body and Hygiene lever L. 100mm.

M1/2" bottom shower outlet.

Wall-mounted mixer with offset STOP/CHECK connectors, M1/2" M3/4".

Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics

- Sliding shower head holder (ref. 813) on a chrome-plated riser rail (ref. 821) with soap dish and flexible shower hose (ref. 836T1).
- Shower head retaining collar (ref. 830).

Suitable for people with reduced mobility.

30-year warranty.

TECHNICAL CHARACTERISTICS

Shower kit with thermostatic mixer - Ref. H9630KIT

Connector	M1/2"
Technology	SECURITHERM single control, Securitouch
Depth	185mm
Length	184mm
Flow rate	9 lpm
Temperature limiter	39°C
Finish	Chrome-plated brass
Norms	ACS



ADVANTAGES



Sequential: opens/closes with cold




Maximum hygiene: no non-return



SECURITHERM: optimal anti-scalding safety



Thermostatic: complete temperature stability



DELABIE

Warranty	30 S WASRANTY
Repairability	50 g

© DELABIE https://www.delabie.co.uk