

## Pre-rinse set with mixer

Ref. 5625

With bib tap and swivelling telescopic spout

2025 UK public price excluding VAT: £940.59

### DESCRIPTION

Pre-rinse set with mixer - Ref. 5625

Complete pre-rinse set with bib tap.  
Single hole deck-mounted mixer with slimline control lever.  
Suitable for intensive use in professional kitchens.  
Mixer supplied with F3/8" flexible hoses and non-return valves.  
Bib tap with swivelling, tubular spout L. 200mm.  
- 16 lpm full flow rate achieved within 90° turn.  
- valve head with reinforced mechanism and ergonomic control.  
Black hand spray with adjustable jet and 9 lpm flow rate at the outlet (ref. 433010).  
Scale-resistant hand spray with shock-resistant tip.  
Reinforced, food-grade black flexible hose L. 0.95m.  
3/4" stainless steel column.  
Adjustable wall bracket.  
Stainless steel spring guide.  
Pre-rinse set with 30-year warranty.

### TECHNICAL CHARACTERISTICS

Pre-rinse set with mixer - Ref. 5625

|                   |                                                                                                                                                                             |
|-------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connector         | F3/8"                                                                                                                                                                       |
| Height            | 1105 - 1225mm                                                                                                                                                               |
| Drop height       | Bib tap: 290mm, hand spray: 460-580mm                                                                                                                                       |
| Flow rate         | Bib tap 16 lpm; 9 lpm via the hand spray                                                                                                                                    |
| Width to the wall | 35 - 162mm                                                                                                                                                                  |
| Finish            | Stainless steel                                                                                                                                                             |
| Norms             | ACS   |
| Warranty          |                                                                                          |
| Repairability     |                                                                                          |



### ADVANTAGES



Anti-torsion rotating nuts and PVC sheath



Comfort: ergonomic control, swivelling spout



Rapid-fill: full flow rate within the first 90°



Hygiene: PVC flexible, scale-resistant spray

