

SECURITHERM shower panel

Ref. 792380

Thermostatic mechanical dual control

2025 UK public price excluding VAT: £1,038.95

DESCRIPTION

SECURITHERM shower panel - Ref. 792380

Dual control thermostatic shower panel:
Anodised aluminium shower panel for wall-mounted, exposed installation.
Concealed inlet via flexibles M $\frac{1}{2}$ ".
SECURITHERM thermostatic mixer.
Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.
Anti-scalding failsafe: automatic shut-off if cold water fails.
Anti-cold showers function: automatic shut-off if hot water fails.
Thermal shocks are possible.
Non-time flow 1/4-turn valves to control flow.
Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation set at 6 lpm at 3 bar.
Handset with removable flexible via push-fit rapid STOP connector and wall support supplied.
Concealed fixings.
Filters and non-return valves.
Suitable for people with reduced mobility.
30-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM shower panel - Ref. 792380

Connector	M $\frac{1}{2}$ "
Technology	Non-time flow
Height	1050mm
Depth	67mm
Width	210mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Aluminium
Norms	   
Warranty	



ADVANTAGES

-  Thermostatic control
-  Instant shut-off if cold water fails
-  Fixed shower head or handset
-  Aluminium panel, brass controls

