

# TEMPOMIX time flow shower kit

Ref. 790709

Single control time flow

2025 UK public price excluding VAT: £448.70

## DESCRIPTION

TEMPOMIX time flow shower kit - Ref. 790709

Recessed time flow shower kit:  
Stainless steel wall plate 160 x 160mm.  
Standard recessing housing.  
Recessing depth can be adjusted from 28 to 48mm.  
TEMPOMIX ¾" single control mixer.  
Ligature-resistant collar.  
Temperature control and operation via the push-button.  
Maximum temperature limiter (can be adjusted by the installer).  
Time flow ~30 seconds, soft-touch operation.  
Flow rate 6 lpm at 3 bar.  
Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.  
M½" connections for copper tubes Ø 14mm.  
Integrated non-return valves and filters.  
Chrome-plated metal control.  
30-year warranty.  
This model does not have a waterproof recessing box. The installer must ensure that the recessing area is waterproof and any leaks or condensates can drain away (see installation guide).

## TECHNICAL CHARACTERISTICS

TEMPOMIX time flow shower kit - Ref. 790709

|            |                                                                                                                                                                             |
|------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connector  | ½"                                                                                                                                                                          |
| Technology | Time flow                                                                                                                                                                   |
| Height     | 160mm                                                                                                                                                                       |
| Width      | 160mm                                                                                                                                                                       |
| Flow rate  | 6 lpm                                                                                                                                                                       |
| Norms      | ACS   |
| Warranty   |                                                                                          |



## ADVANTAGES



80% water savings



Wall recessed installation



Time flow system tested to over 500,000 operations



Soft-touch operation

