

## PREMIX SECURITY Group thermostatic mixing valve

Ref. 731052

For circulating loops 44°-58°C

2022 UK public price excluding VAT: £528.62



### DESCRIPTION

PREMIX SECURITY Group thermostatic mixing valve - Ref. 731052

Group thermostatic mixing valve for hot water circulating loops adjustable from 44°C to 58°C:

Anti-scalding safety.

Regulates temperature variations.

Non-return valves and filters accessible from the exterior without having to remove the mechanism.

Thermal cartridge with no specific lever needed (push-button on the control knob).

Interchangeable cartridge with thermostatic cell.

High-resistance chrome-plated brass body.

Maximum hot water temperature: 85°C.

Differential hot water / mixed water: 15°C mini.

Pressure differences at the entrance: 1 bar maximum (0.5 bar recommended).

Minimum pressure / maximum: 1 to 10 bar (1 to 5 bar recommended).

Left hand side hot water inlet (red ring) and right hand side cold water inlet (blue ring).

Mixed water outlet at the top (purple ring) for bottom outlet: unscrew / place lid at the top and outlet connector at the bottom.

15% energy savings: optimised heat loss (comparison between a circulating loop at 55°C and a non-circulating system at 70°C).

Safety and prolongation of system life span (Hot water > 65°C leads to premature aging within the system).

Maximum temperature limiter, can be adjusted by the installer.

Reduced risk of scalding by limiting temperature at the point-of-use.

55 lpm - M<sup>3</sup>/<sub>4</sub>".

10-year warranty.

### ADVANTAGES



Automatic shut-off if cold water fails



Temperature stability






Accessible filters and non-return valves



Automotive thermo-reactive cell

### TECHNICAL CHARACTERISTICS

PREMIX SECURITY Group thermostatic mixing valve - Ref. 731052

Connector	M <sup>3</sup> / <sub>4</sub> "
Technology	Thermostatic
Height	60mm
Depth	18mm
Length	120mm
Flow rate	55 lpm
Norms	  
Warranty	