

# PREMIX COMFORT Group thermostatic mixing valve

Ref. 731004

For mixed water 32°-42°C

2026 UK public price excluding VAT: £1,485.86



## DESCRIPTION

PREMIX COMFORT Group thermostatic mixing valve - Ref. 731004

Group thermostatic mixing valve for mixed water from 32° to 42°C:  
Anti-scalding safety.  
Regulation of temperature variations.  
Non-return valves and filters accessible from the exterior without having to remove the mechanism.  
Thermal cartridge with no specific lever needed (push-button on the control knob).  
Interchangeable cartridge with thermo-reactive cell.  
High-resistance chrome-plated brass body.  
Maximum hot water temperature: 85°C.  
Differential hot water / mixed water: 15°C mini.  
Pressure differences at the entrance: 1 bar maximum (0.5 bar recommended).  
Minimum pressure / maximum: 1 to 10 bar (1 to 5 bar recommended).  
Left hand side hot water inlet (red ring) and right hand side cold water inlet (blue ring).  
Mixed water outlet at the top (purple ring).  
For bottom outlet: unscrew / place lid at the top and outlet connector at the bottom.  
Maximum temperature limiter, can be adjusted by the installer.  
Reduced risk of scalding by limiting temperature at the point-of-use.  
140 lpm - M1¼".  
30-year warranty.

## ADVANTAGES



Automatic shut-off if cold water supply fails



Temperature stability



Accessible filters and non-return valves



Thermo-reactive cell

## TECHNICAL CHARACTERISTICS

PREMIX COMFORT Group thermostatic mixing valve - Ref. 731004

Connector	M1¼"
Technology	Thermostatic
Height	90mm
Depth	26mm
Length	180mm
Flow rate	140 lpm
Norms	  
Warranty	
Repairability	

