

PREMIX COMFORT

Ref. 731200

Group thermostatic mixing valve, mixed water 32°-42°C

2026 UK public price excluding VAT: £667.80



DESCRIPTION

PREMIX COMFORT - Ref. 731200

Group thermostatic mixing valve for mixed water from 32° to 42°C:
 Anti-scalding safety.
 Regulation of temperature variations.
 Non-return valves and filters accessible from the exterior without having to remove the mechanism.
 Thermal cartridge with no specific lever needed (push-button on the control knob).
 Interchangeable cartridge with thermo-reactive cell.
 High-resistance chrome-plated brass body.
 Maximum hot water temperature: 85°C.
 Differential hot water / mixed water: 15°C mini.
 Pressure differences at the entrance: 1 bar maximum (0.5 bar recommended).
 Minimum pressure / maximum: 1 to 10 bar (1 to 5 bar recommended).
 Left hand side hot water inlet (red ring) and right hand side cold water inlet (blue ring).
 Mixed water outlet at the top (purple ring).
 For bottom outlet: unscrew / place lid at the top and outlet connector at the bottom.
 Maximum temperature limiter, can be adjusted by the installer.
 Reduced risk of scalding by limiting temperature at the point-of-use.
 55 lpm - M^{3/4}".
 30-year warranty.

TECHNICAL CHARACTERISTICS

PREMIX COMFORT - Ref. 731200

Connector	M ^{3/4} "
Technology	Thermostatic
Height	81mm
Depth	18mm
Length	120mm
Flow rate	55 lpm
Norms	  
Warranty	
Repairability	

ADVANTAGES

-  Automatic shut-off if cold water supply fails
-  Temperature stability
-  Accessible filters and non-return valves
-  Thermo-reactive cell

