

PREMIX COMPACT

Thermostatic mixing valve

Ref. 733015

For mixed water 30 - 60°C

2026 UK public price excluding VAT: £127.56



DESCRIPTION

PREMIX COMPACT Thermostatic mixing valve - Ref. 733015

PREMIX COMPACT thermostatic mixing valve for mixed water distribution from 30 - 60°C:

For 1 to 11 points-of-use (depending on the flow rate).

Anti-scalding safety: immediate shut-off if cold water fails.

Anti-cold shower function - automatic shut-off if hot water supply fails.

Adjustable temperature from 30 - 60°C, can be blocked by the installer.

Brass body.

Filters and non-return valves.

Recommended flow rate range: from 5 - 33 lpm.

Thermal shocks are possible.

M $\frac{1}{2}$ ".

40mm centres.

30-year warranty.

ADVANTAGES



Automatic shut-off if cold water fails



Temperature stability



Accessible filters and non-return valves



Thermo-reactive cell

TECHNICAL CHARACTERISTICS

PREMIX COMPACT Thermostatic mixing valve - Ref. 733015

Connector	M $\frac{1}{2}$ "
Technology	Thermostatic
Length	120mm
Finish	Nickel-plated
Norms	    
Warranty	
Repairability	

