

PREMIX COMPACT

Thermostatic mixing valve

Ref. 733020

For mixed water 30 - 60°C

2026 UK public price excluding VAT: £127.56



DESCRIPTION

PREMIX COMPACT Thermostatic mixing valve - Ref. 733020

Thermostatic mixing valve for mixed water distribution from 30 - 60°C:
For 1 to 11 sanitary points-of-use (depending on the flow rate).
Anti-scalding safety: immediate shut-off if cold water supply fails.
Cold shower failsafe: automatic shut-off if hot water supply fails.
Adjustable temperature from 30 - 60°C, can be blocked by the installer.
Brass body.
Filters and non-return valves.
Minimum flow rate to operate: from 5 - 33 lpm.
Thermal shocks are possible.
M $\frac{3}{4}$ ".
40mm centres.
30-year warranty.

ADVANTAGES



Automatic shut-off if cold or hot water fails



Temperature stability



Accessible filters and non-return valves



Thermo-reactive cell

TECHNICAL CHARACTERISTICS

PREMIX COMPACT Thermostatic mixing valve - Ref. 733020

Connector	M $\frac{3}{4}$ "
Technology	Thermostatic
Length	120mm
Finish	Nickel-plated
Norms	     
Warranty	
Repairability	

