

TEMPOMATIC WC direct flush valve

Ref. 463150

Direct flush WC valve

2026 UK public price excluding VAT: £922.65



DESCRIPTION

TEMPOMATIC WC direct flush valve - Ref. 463150

Flush system without cistern: directly connected to pipework.
Mains supply with 1" solenoid valve.
230/12V transformer.
IP65 independent electronic unit.
For installation on walls ≤ 160 mm.
Shock-resistant infrared presence detection sensor.
Voluntary activation (when hand is detected ~ 4 cm in front of sensor) or automatic flush when user leaves.
Time flow ~ 7 seconds, can be adjusted from 3 - 12 seconds.
Detection distance, flow rate and flush volume can be adjusted.
Stopcock FF1".
Vacuum breaker $\varnothing 32$ mm.
Connection washer $\varnothing 32/55$ mm.
Wall plate flush to the wall.
Threaded tube can be cut to size.
Base flow rate: 1 L/sec at 1 bar dynamic.
Compatible with rain water, sea water and gray water.
Suitable for rimless WC pans without flow rate regulation and suitable for people with reduced mobility.
30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOMATIC WC direct flush valve - Ref. 463150

Supply	230/12V mains supply
Connector	1"
Technology	Electronic
Length	160mm
Norms	 
Warranty	
Repairability	

ADVANTAGES



Total hygiene: operate without manual contact



No cistern: no stagnant water



Voluntary or automatic activation



Cross wall installation

