

TEMPOFLUX 2 direct flush valve

Ref. 762150

Direct flush WC valve

2025 UK public price excluding VAT: £288.48







DESCRIPTION

TEMPOFLUX 2 direct flush valve - Ref. 762150



Flush system without cistern: directly connected to pipework.
 For walls ≤ 140mm.
 3L/6L dual flush can be adjusted to 2L/4L.
 Soft-touch operation.
 Vacuum breaker.
 Integrated stopcock and flow rate / flush volume adjuster.
 Solid brass body.
 Chrome-plated metal push-button.
 In-line inlet M $\frac{3}{4}$ ".
 Outlet connection for PVC tube Ø 26/32mm.
 Threaded rod can be cut to size.
 Acoustic level complies with European standard EN 12541 class II.
 Upstream supply pipes: minimum Ø 20mm required at all points (including connectors).
 Base flow rate: 1 L/sec at 1 bar dynamic pressure.
 Compatible with rain water.
 Suitable for rimless WC pans without flow rate regulation.
 Suitable for people with reduced mobility.
 30-year warranty.

ADVANTAGES

-  Soft-touch operation
-  Dual flush 3L/6L
-  No cistern: no stagnant water
-  Cross wall installation

TECHNICAL CHARACTERISTICS

TEMPOFLUX 2 direct flush valve - Ref. 762150

Connector	$\frac{3}{4}$ "
Technology	Time flow
Length	140mm
Flow rate	3L/6L
Norms	 
Warranty	