TEMPOFLUX 2 direct flush valve

Ref. 762150

Direct flush WC valve

2024 UK public price excluding VAT: £280.08



DESCRIPTION

TEMPOFLUX 2 direct flush valve - Ref. 762150

Flush system without cistern: directly connected to pipework.

For walls ≤ 140mm.

3L/6L dual flush can be adjusted to 2L/4L.

Soft-touch operation.

Vacuum breaker.

Integrated stopcock and flow rate / flush volume adjuster.

Solid brass body.

Chrome-plated metal push-button.

In-line inlet M¾".

Outlet connection for PVC tube Ø 26/32mm.

Threaded rod can be cut to size.

Acoustic level complies with European standard EN 12541 class II.

Upstream supply pipes: minimum \emptyset 20mm required at all points (including connectors).

Base flow rate: 1 L/sec at 1 bar dynamic pressure.

Compatible with rain water.

Suitable for rimless WC pans without flow rate regulation.

Suitable for people with reduced mobility.

30-year warranty.

ADVANTAGES



Soft-touch operation



Dual flush 3L/6L



No cistern: no stagnant water



Cross wall installation

TECHNICAL CHARACTERISTICS

TEMPOFLUX 2 direct flush valve - Ref. 762150

Connector	3/4"
Technology	Time flow
Length	140mm
Flow rate	3L/6L
Norms	<u></u> B
Warranty	30 WARRANTY

