TEMPOFLUX 2 direct flush valve

Ref. 762901

Time flow direct flush WC valve

2025 UK public price excluding VAT: £279.06



TEMPOFLUX 2 direct flush valve - Ref. 762901

Flush system without cistern: directly connected to pipework.

Chrome-plated metal wall plate Ø 195mm.

Concealed mechanical fixing of the wall plate.

Multipurpose recessing housing.

Recessing depth can be adjusted from 0 - 20mm.

6L single flush.

Soft-touch operation.

Vacuum breaker.

Integrated stopcock and flow rate / flush volume adjuster.

Solid brass body.

Chrome-plated metal push-button.

In-line inlet M¾".

Outlet connection for PVC tube Ø 26/32mm.

Acoustic level complies with European standard EN 12541 class II.

Upstream supply pipes: minimum \emptyset 20mm required at all points (including connectors).

Base flow rate: 1 L/sec at 1 bar dynamic pressure.

Compatible with rain water.

Suitable for rimless WC pans without flow rate regulation and suitable for people with reduced mobility.

30-year warranty.

This model does not have a waterproof recessing housing. The installer must ensure that the recessing area is waterproof and any leaks or condensation can drain away (see installation guide).

TECHNICAL CHARACTERISTICS

TEMPOFLUX 2 direct flush valve - Ref. 762901

Connector	3/4"
Technology	Time flow
Flow rate	61
Finish	Chrome-plated metal
Norms	BELGADUA
Warranty	30 g



ADVANTAGES



Soft-touch operation



No cistern: no stagnant water



Wall recessed installation



Powerful flush and available immediately

