

# SECURITHERM shower panel

Ref. 792305

Thermostatic time flow

2025 UK public price excluding VAT: £926.88





## DESCRIPTION

**SECURITHERM shower panel** - Ref. 792305

Thermostatic time flow shower panel:  
Anodised aluminium shower panel for wall-mounted, exposed installation.  
With top inlet via in-line stopcocks M1/2".  
SECURITHERM thermostatic mixer.  
Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.  
Anti-scalding failsafe: automatic shut-off if cold water fails.  
Anti-cold showers function: automatic shut-off if hot water fails.  
Thermal shocks are possible.  
Soft-touch operation.  
Time flow ~30 seconds.  
Flow rate set at 6 lpm at 3 bar.  
Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.  
With soap dish.  
Concealed fixings.  
Filters and non-return valves.  
Suitable for people with reduced mobility.  
30-year warranty.





## TECHNICAL CHARACTERISTICS

**SECURITHERM shower panel** - Ref. 792305

Connector	M1/2"
Technology	Time flow
Height	1050mm
Depth	65mm
Width	210mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Aluminium
Norms	  
Warranty	



## ADVANTAGES

-  Thermostatic temperature regulation
-  Instant shut-off if cold water fails
-  80% water savings
-  Aluminium panel, brass controls

