

# TEMPOMATIC electronic shower kit

Ref. 452159

Electronic

2026 UK public price excluding VAT: £561.89



## DESCRIPTION

TEMPOMATIC electronic shower kit - Ref. 452159

Cross wall electronic shower kit:  
TEMPOMATIC electronic valve for mixed water supply.  
For walls ≤ 155mm.  
Power supply by electronic unit with solenoid valve 1/2".  
230/12V transformer.  
2 operation modes:  
- Automatic activation via presence detection.  
- Voluntary ON/OFF activation by passing the hand in front of sensor ~10 cm.  
Duty flush (~60 seconds every 24 hours after the last use).  
Adjustable time flow from 30 to 60 seconds.  
Flow rate set at 6 lpm at 3 bar.  
Chrome-plated, tamperproof, scale-resistant ROUND shower head with automatic flow rate regulation.  
Chrome-plated solid brass.  
Wall plate flush to the wall.  
Threaded rods can be cut-to-size.  
Electronic shower kit suitable for people with reduced mobility.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

TEMPOMATIC electronic shower kit - Ref. 452159

|            |                                                                                                                                                                                                                                                             |
|------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Supply     | 230/12V mains supply                                                                                                                                                                                                                                        |
| Connector  | 1/2"                                                                                                                                                                                                                                                        |
| Technology | Electronic                                                                                                                                                                                                                                                  |
| Length     | 155mm                                                                                                                                                                                                                                                       |
| Flow rate  | 6 lpm                                                                                                                                                                                                                                                       |
| Norms      |    |
| Warranty   |                                                                                                                                                                          |

## ADVANTAGES



230/12V



Total hygiene: no manual contact



Anti-bacterial duty flush



2 operation modes

