

# TEMPOFLUX time flow urinal valve

Ref. 778755

Time flow 3 seconds. For standard urinals Ø 35mm. Straight neck tube

2025 UK public price excluding VAT: £169.18

## DESCRIPTION

TEMPOFLUX time flow urinal valve - Ref. 778755

Exposed time flow urinal valve:  
For standard or siphon action urinals.  
For wall-mounted exposed installation.  
Soft-touch operation.  
Time flow pre-set at 3 seconds.  
Vacuum breaker.  
Flow rate pre-set at 0.15 l/sec. at 3 bar, can be adjusted up to 0.3 l/sec.  
Innovative stopcock and flow rate adjustment system integrated in the wall plate (patented).  
Compatible with rain water.  
Complies with European standard EN 12541 (acoustic level class II).  
Chrome-plated solid brass body M½".  
With a chrome-plated neck tube and connection washer Ø 35mm.  
Angled for recessed inlet.  
Suitable for people with reduced mobility.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

TEMPOFLUX time flow urinal valve - Ref. 778755

|            |                                                                                                                                                                         |
|------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connector  | ½"                                                                                                                                                                      |
| Technology | Time flow                                                                                                                                                               |
| Height     | 320mm                                                                                                                                                                   |
| Flow rate  | 0.15 l/sec.                                                                                                                                                             |
| Norms      |   |
| Warranty   |                                                                                      |



## ADVANTAGES



Eco time flow 3 seconds



Soft-touch operation



Stopcock built-in to wall plate



Smooth design

