

TEMPOFLUX time flow urinal valve

Ref. 778755

Time flow 3 seconds. For standard urinals Ø 35mm. Straight neck tube

2025 UK public price excluding VAT: £169.18

DESCRIPTION

TEMPOFLUX time flow urinal valve - Ref. 778755

Exposed time flow urinal valve:
For standard or siphon action urinals.
For wall-mounted exposed installation.
Soft-touch operation.
Time flow pre-set at 3 seconds.
Vacuum breaker.
Flow rate pre-set at 0.15 l/sec. at 3 bar, can be adjusted up to 0.3 l/sec.
Innovative stopcock and flow rate adjustment system integrated in the wall plate (patented).
Compatible with rain water.
Complies with European standard EN 12541 (acoustic level class II).
Chrome-plated solid brass body M½".
With a chrome-plated neck tube and connection washer Ø 35mm.
Angled for recessed inlet.
Suitable for people with reduced mobility.
30-year warranty.

TECHNICAL CHARACTERISTICS

TEMPOFLUX time flow urinal valve - Ref. 778755

Connector	½"
Technology	Time flow
Height	320mm
Flow rate	0.15 l/sec.
Norms	 
Warranty	



ADVANTAGES



Eco time flow 3 seconds



Soft-touch operation



Stopcock built-in to wall plate



Smooth design

