

# TEMPOMIX time flow shower mixer

Ref. 790925

Single control time flow

2026 UK public price excluding VAT: £368.22



## DESCRIPTION

TEMPOMIX time flow shower mixer - Ref. 790925

Recessed time flow shower kit:  
 Chrome-plated Ø 195mm wall plate.  
 Standard recessing housing.  
 Recessing depth adjustable from 28 - 43mm.  
 TEMPOMIX ¼" single control mixer.  
 Ligature-resistant collar.  
 Temperature control and operation via the push-button.  
 Maximum temperature limiter (can be adjusted by the installer).  
 Time flow ~30 seconds, soft-touch operation.  
 Flow rate 12 lpm at 3 bar.  
 M½" connectors for Ø 15mm copper tubes.  
 Integrated non-return valves and filters.  
 Chrome-plated metal control.  
 30-year warranty.  
 As this model does not come with waterproof recessing housing the installer must ensure the watertightness of the recessing area and allow for run-off of leaks and condensation (see installation guide).

## TECHNICAL CHARACTERISTICS

TEMPOMIX time flow shower mixer - Ref. 790925

|            |                                                                                                                                                                                                                                                                                                                                                 |
|------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connector  | M1/2" Ø 15mm                                                                                                                                                                                                                                                                                                                                    |
| Technology | Time flow                                                                                                                                                                                                                                                                                                                                       |
| Flow rate  | 12 lpm                                                                                                                                                                                                                                                                                                                                          |
| Norms      |     |
| Warranty   |                                                                                                                                                                                                                                                              |

## ADVANTAGES



Recessed wall installation



Time flow system tested to 500,000+ operations



Soft-touch operation

