

# TEMPOMIX 3 time flow shower mixer

Ref. 794400

Time flow single control

2026 UK public price excluding VAT: £319.99



## DESCRIPTION

TEMPOMIX 3 time flow shower mixer - Ref. 794400

Exposed time flow shower mixer:  
TEMPOMIX 3 single control mixer, top outlet M $\frac{3}{4}$ ".  
For wall-mounted, exposed installation.  
Temperature control and operation via the push-button.  
Maximum temperature limiter (can be adjusted by the installer).  
Soft-touch operation.  
Pre-set time flow ~30 seconds, adjustable from 20 to 30 seconds.  
Flow rate 6 lpm at 3 bar, can be adjusted from 6 - 12 lpm.  
Chrome-plated brass.  
Integrated filters and non-return valves.  
Chrome-plated metal push-button.  
M $\frac{1}{2}$ " offset connectors for 130 - 170mm centres.  
Suitable for people with reduced mobility.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

TEMPOMIX 3 time flow shower mixer - Ref. 794400

|               |                                                                                                                                                                                                                                                                                                                                                 |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connector     | M $\frac{1}{2}$ "                                                                                                                                                                                                                                                                                                                               |
| Technology    | Time flow                                                                                                                                                                                                                                                                                                                                       |
| Width         | 150mm                                                                                                                                                                                                                                                                                                                                           |
| Flow rate     | 9 lpm                                                                                                                                                                                                                                                                                                                                           |
| Norms         |     |
| Warranty      |                                                                                                                                                                                                                                                              |
| Repairability |                                                                                                                                                                                                                                                              |

## ADVANTAGES



Soft-touch operation



Time flow system tested to over 500,000 operations

