

# PREMIX NANO thermostatic mixing valve

Ref. 732115

For mixed water from 34 - 60°C

2026 UK public price excluding VAT: £96.69



## DESCRIPTION

PREMIX NANO thermostatic mixing valve - Ref. 732115

Hot water thermostatic mixing valve for mixed water distribution from 34 - 60°C:

For 1 - 2 taps or 1 shower.

Anti-scalding safety: immediate shut-off if cold or hot water fails.

Temperature pre-set at 38°C, can be adjusted by the installer from 34 - 60°C.

Brass body.

Filters and non-return valves.

Minimum flow rate to operate: 3 lpm.

Thermal shocks are possible.

Nickel-plated brass body M $\frac{1}{2}$ " inlets and Ø 15mm conical outlets.

30-year warranty.

## ADVANTAGES



Automatic shut-off if hot or cold water fails



Stable temperature



Non-return valves and filters easily accessible



Thermo-reactive cell

## TECHNICAL CHARACTERISTICS

PREMIX NANO thermostatic mixing valve - Ref. 732115

|               |                                                                                     |
|---------------|-------------------------------------------------------------------------------------|
| Connector     | M $\frac{1}{2}$ " Ø 15mm                                                            |
| Technology    | Thermostatic                                                                        |
| Height        | 70mm                                                                                |
| Finish        | Nickel-plated                                                                       |
| Norms         |  |
| Warranty      |  |
| Repairability |  |

