

SECURITHERM BIOCLIP

thermostatic basin mixer

Ref. H960515L

Single hole sequential thermostatic control mixer H. 95mm L. 120mm

2026 UK public price excluding VAT: £459.87

DESCRIPTION

SECURITHERM BIOCLIP thermostatic basin mixer - Ref. H960515L

Deck-mounted SECURITHERM thermostatic basin mixer.
Sequential thermostatic mixer: opens and closes with cold water.
No risk of cross flow between hot and cold water.
No non-return valves on the inlets.
BIOCLIP: can be easily removed for cleaning and disinfection.
Anti-scalding failsafe: shuts off immediately if cold or hot water supply fails.
Securitouch thermal insulation prevents burns.
Single hole mixer with curved spout, H. 95mm L. 120mm, fitted with a hygienic flow straightener, no build-up of impurities and withstands thermal shocks.
Scale-resistant thermostatic sequential cartridge for single control adjustment of flow rate and temperature.
Temperature adjusts from cold water up to 40°C with maximum temperature limiter set at 40°C.
Tested without water to comply with NHS requirements. No pre-set temperature.
Thermal and chemical shocks are possible.
Body and spout with smooth interior and low water volume.
Flow rate limited to 5 lpm at 3 bar.
No manual contact thanks to Hygiene control lever L. 100mm.
With no pop-up waste.
Supplied with F3/8" PEX flexibles with chrome-plated brass stopcocks.
Fixing reinforced via 2 stainless steel rods.
Mixer ideal for healthcare facilities, retirement and care homes, hospitals and clinics.
Mixer suitable for people with reduced mobility.
Mixer with 30-year warranty.
Also available with copper tails.

TECHNICAL CHARACTERISTICS


SECURITHERM BIOCLIP thermostatic basin mixer - Ref. H960515L

Connector	M1/2", Ø 15mm
Technology	Single control BIOCLIP SECURITHERM, Securitouch
Drop height	95mm
Spout length	120mm
Flow rate	5 lpm at 3 bar
Temperature limiter	Yes
Finish	Chrome-plated brass



ADVANTAGES

- Maximum hygiene: mixer with no non-return valves
- Hygiene: can be removed for internal cleaning
- SECURITHERM: optimal anti-scalding safety
- Sequential: opens/closes with cold water



Norms



Warranty



Repairability

