

# BINOPTIC MIX electronic mixer

Ref. 478MCH15

Battery operated, Ø 15mm compression fittings

2025 UK public price excluding VAT: £696.63

## DESCRIPTION

**BINOPTIC MIX electronic mixer - Ref. 478MCH15**

Deck-mounted electronic basin mixer:  
Independent IP65 electronic control unit.  
123 6V Lithium battery.  
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.  
Scale-resistant flow straightener.  
Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).  
Active, infrared movement detection, sensor at the end of the spout optimises detection.  
Chrome-plated solid brass body.  
PEX flexibles with filters, solenoid valves and Ø 15mm compression fittings.  
Fixing reinforced by 2 stainless steel rods.  
Anti-blocking security.  
Spout with a smooth interior and low volume of water (limits bacterial niches).  
Side temperature control with adjustable maximum temperature limiter.  
30-year warranty.

## TECHNICAL CHARACTERISTICS

**BINOPTIC MIX electronic mixer - Ref. 478MCH15**

|               |                                                                                     |
|---------------|-------------------------------------------------------------------------------------|
| Supply        | 6V battery                                                                          |
| Connector     | M1/2" Ø 15mm                                                                        |
| Technology    | Electronic                                                                          |
| Drop height   | 110mm                                                                               |
| Spout length  | 135mm                                                                               |
| Flow rate     | 3 lpm                                                                               |
| Warranty      |  |
| Repairability |  |



## ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Duty flush limits bacterial proliferation



LED diagnostic aid

