

BINOPTIC MIX electronic mixer

Ref. 478MCH15

Battery operated, Ø 15mm compression fittings

2025 UK public price excluding VAT: £696.63



DESCRIPTION

BINOPTIC MIX electronic mixer - Ref. 478MCH15

Deck-mounted electronic basin mixer:
Independent IP65 electronic control unit.
123 6V Lithium battery.
Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.
Scale-resistant flow straightener.
Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).
Active, infrared movement detection, sensor at the end of the spout optimises detection.
Chrome-plated solid brass body.
PEX flexibles with filters, solenoid valves and Ø 15mm compression fittings.
Fixing reinforced by 2 stainless steel rods.
Anti-blocking security.
Spout with a smooth interior and low volume of water (limits bacterial niches).
Side temperature control with adjustable maximum temperature limiter.
30-year warranty.

TECHNICAL CHARACTERISTICS

BINOPTIC MIX electronic mixer - Ref. 478MCH15

Supply	6V battery
Connector	M1/2" Ø 15mm
Technology	Electronic
Drop height	110mm
Spout length	135mm
Flow rate	3 lpm
Warranty	
Repairability	

ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Duty flush limits bacterial proliferation



LED diagnostic aid

