BINOPTIC electronic tap

Ref. 47801515

Battery-operated, Ø 15mm compression fittings

2025 UK public price excluding VAT: £534.88



DESCRIPTION

BINOPTIC electronic tap - Ref. 47801515

Deck-mounted electronic basin tap:

Independent IP65 electronic control unit.

123 6V Lithium battery.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.

Scale-resistant flow straightener.

Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use). Active, infrared movement detection, sensor at the end of the spout optimises detection.

Chrome-plated solid brass body.

PEX flexible with filter, solenoid valve and Ø 15mm compression fittings.

Fixing reinforced by 2 stainless steel rods.

Anti-blocking security.

Spout with a smooth interior and low volume of water (limits bacterial niches).

Suitable for people with reduced mobility.

30-year warranty.

ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Duty flush limits bacterial proliferation




LED diagnostic aid

TECHNICAL CHARACTERISTICS

BINOPTIC electronic tap - Ref. 47801515

Supply	6V battery
Connector	M1/2" Ø 15mm
Technology	Electronic
Drop height	90mm
Spout length	125mm
Flow rate	3 lpm
Warranty	30 g



© DELABIE