

BINOPTIC MIX electronic mixer

Ref. 379MCH15

Mains supply, Ø 15mm compression fittings

2026 UK public price excluding VAT: £622.64



DESCRIPTION

BINOPTIC MIX electronic mixer - Ref. 379MCH15

Cross wall electronic basin mixer:

Independent IP65 electronic control unit.

230/12V mains supply with transformer.

Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 to 6 lpm.

Scale-resistant flow straightener.

Duty flush (~60 sec. every 24h after last use).

Active, infrared movement detection, sensor at the end of the spout optimises detection.

Filters, solenoid valves, and Ø 15mm compression fittings.

Chrome-plated solid brass body.

Chrome plated spout for cross wall installations ≤ 110mm.

Cable for sensor L.120mm, flexibles and mounting all pass through the same hole.

Anti-blocking security.

Spout with a smooth interior and low volume of water (limits bacterial niches).

Side temperature control with adjustable maximum temperature limiter.

Suitable for people with reduced mobility.

30-year warranty.

TECHNICAL CHARACTERISTICS

BINOPTIC MIX electronic mixer - Ref. 379MCH15

Supply	230/12V mains supply
Connector	M1/2" Ø 15mm
Technology	Electronic
Spout length	230mm
Flow rate	3 lpm
Norms	 
Warranty	

ADVANTAGES



Exceptional water savings: 90%



Hygiene: no manual contact



Duty flush limits bacterial proliferation



LED diagnostic aid

